

TWO PIECE AND ASSEMBLEABLE
SLIDER FOR APPLICATION TO RESEALABLE
PORTIONS ASSOCIATED WITH A PLASTIC BAG

BACKGROUND OF THE INVENTION

5 FIELD OF THE INVENTION

 The present invention relates generally to slider mechanisms for use with opposing and interengaging reclosable portions associated with a resealable plastic bag. More specifically, the present invention discloses an assembleable and two-piece slider mechanism incorporating a main body
10 exhibiting a central splitter portion and two hingedly attached and foldable wing portions. A substantially “U” shaped and assembleable cap portion is engaged over the main body upon the same being pre-positioned relative to the extending reclosable portions.

DESCRIPTION OF THE PRIOR ART

15 The prior art is well documented with various examples of slider mechanisms and such as which are specifically employed with opposingly extending and reclosable portions associated with such as a resealable plastic bag. The objective in each instance is the production of a slider mechanism, capable of quickly and efficiently being secured to the reclosable portions and
20 which is traversable to quickly unseal and reseal the bag.

 U.S. Patent No. 5,448,808, issued to Gross, teaches a foldable zipper slider with improved compression-type latching. In particular, the zipper slider includes hinged wings provided with an improved latch tongue which is deflected downward to snap in place. Additional flexible latch web structure

cooperates with the latch tongue to provide additional forces which are active in assuring that the wings are fully latched and to also provide additional resistance to unlatching the wings.

U.S. Patent No. 5,867,875, issued to Beck et al., teaches a foldable
5 zipper slider for straddling relation with a profiled plastic zipper. The straddling slider actuates to close or open the zipper by movement therealong and includes a transverse support member including opposing sides, a pair of legs depending from the opposing sides of the support member, and a pair of wings hingedly attached to the opposing sides. Each wing has an opening for
10 receiving its respective leg, and each further includes a cored out cross piece exhibiting a solid ramp latch. The wings are folded relative to the support member and the latches engage the legs to assemble the slider on the zipper in a closed sidewall position.

U.S. Patent No. 5,070,583, issued to Herington, teaches a foldable
15 plastic slider having a pair of hinged wings that fold downwardly and are secured permanently in place to the opposite sides of a slider body to attach it to the plastic reclosable fastener elements when manufacturing a thermoplastic bag. The wings are hinged at the top of the slider body to provide for ease in molding the slider using a simple two-piece mold. Additional examples of
20 foldable zipper assemblies are also illustrated in Herrington 5,063,644 and Herrington 5,131,121.

U.S. Patent No. 5,283,932, issued to Richardson, teaches a flexible plastic slider having sidewalls normally diverging outwardly and spaced apart a

A substantially "U" shaped and assembleable cap portion is engaged over the main body upon the same being pre-positioned with the blade between the reclosable portions and the wings folded in opposing and engaging contact against the sides of the bag and with the narrowed aperture defining a resealing
5 location of the male and female profiles. The exterior surfaces of the foldable wings and interior surfaces of the assembleable cap further define mating surface configurations for securely attaching the cap and the main slider body to the resealable bag.

BRIEF DESCRIPTION OF THE DRAWINGS

10 Reference will now be made to the attached drawings, when read in combination with the following detailed description, wherein like reference numerals refer to like parts throughout the several views, and in which:

Fig. 1 is an environmental view of the two-piece slider assembled over first and second opposing and reclosable portions according to the present
15 invention;

Fig. 2 is an enlarged and rotated perspective view of the assembleable slider in place over the opposingly extending and reclosable portions and such that traversing motion of the slider selectively unseals and reseals the plastic bag;

20 Fig. 3 is a plan view of a first main body of the assembleable slider and exhibiting the features of the central splitter and first and second hingedly attached and foldable wings according to the present invention;

Fig. 4 is a cutaway illustration of the main body, taken along line 4-4 of Fig. 3, and further showing the pre-positioned orientation of the opposing and reclosable portions as well as the assembleable cap;

5 Fig. 5 is a perspective view of an intermediate assembly step by which the cap is illustrated in arrayed and downwardly engageable fashion above the main body in pre-positioned fashion relative to the reclosable portions;

Fig. 6 is an end view of the assembled slider and in particular illustrating the separating action of the blade associated with the central body; and

10 Fig. 7 is a cutaway illustration taken along line 7-7 of Fig. 2, similar in regards to that shown in Fig. 6, and illustrating a substantially central cross sectional arrangement of the assembled slider relative to the opposing and reclosable bag portions.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

15 Referring to Figs. 1-7, an assembleable slider is illustrated at 10 according to a preferred embodiment of the present invention. As previously discussed, the present invention provides a novel and improved two-piece slider, as generally shown at 10, for assembly over and between a pair of oppositely extending and reclosable portions. The reclosable portions are
20 illustrated at 12 and 14 throughout the several views and form a portion of a plastic bag 16 (see as further shown in Figs. 1 and 2).

Each reclosable portion includes an inwardly facing and opposing biasingly engaging profile, see as best shown by female profile 18 for

reclosable portion 12 and by male profile 20 for reclosable portion 14 in Figs. 4, 6 and 7. As is further illustrated in Fig. 1, upper ends of the bag 16 are heat staked or otherwise sealed, see as shown by portions 22 and 24, and define therebetween the extending and reclosable portions 12 and 14.

5 The slider assembly 10 includes a main body, generally illustrated at 26, having a central substantially rectangular shaped portion 28 and first 30 and second 32 extending and foldable wings. The main body 26 is further constructed of a durable plastic material and further such that the wings 30 and 32 are hingedly secured, such as are referenced in Fig. 3 at locations 34 & 36
10 for wing 30 and at locations 38 & 40 for wing 32, to opposite edges of the central portion 28.

 A blade 42 extends downwardly from an associated bottom surface of the central portion 28 and such that, upon pre-positioning of the main body 26 over the bag 16, the blade 42 extends between the male 18 and female 20
15 profiles associated with the reclosable portions 12 and 14 and as is best illustrated in Figs. 2, 6 and 7. At this point, an intermediate assembly step includes the downwardly folding of the wings 30 and 32, from the initial position illustrated in Fig. 4 and along the direction of referenced arrows 44 and 46.

20 Opposing and inwardly directed pincer portions are illustrated at 48 and 50, associated with bottom extending edges of the wings 30 and 32, and bias against opposed facing sides of the bag 16 upon downward folding of the pincer portions. First and second mating portions 52 and 54 integrally extend

from an end of each of the foldable wings 30 and 32, and define therebetween a narrowed aperture 56 through which the biasingly mating male and female profiles 18 and 20 are compressed upon traversing motion of the slider in a selected direction 58 (Fig. 2) relative to an axial direction along the reclosable portions.

In contrast, traversing of the slider body in an opposite direction 60 (again Fig. 2) results in the unsealing of the mating portions 18 and 20 by the blade 42. It is also understood that the folding wings 30 and 32 define therebetween an extending channel along the interior axial length of the main body 26, communicating the blade with the narrowed aperture 56, and it is further envisioned that the geometry of the main body may be altered such that the narrowed aperture is moved to a front or leading edge of the mating portions 52 and 54, and such as which is further illustrated in phantom at 62 in Fig. 2. Referring again to Fig. 4, pairs of bead portions 64 and 66 may extend from opposing edges of the wings 30 and 32 and to better seal against the surfaces of the bag 16.

Referring again to the several views, a substantially “U” shaped cap (typically constructed from the same plastic material as the main body 26) is referenced generally at 68 and includes a central body portion 70 from which extend a first side 72 and a second side 74. The foldable wings 30 and 32 each further include an exteriorly configured surface proximate an upper end thereof and which is shown at 76 and 78. The first and second extending sides 72 and 74 associated with the assembleable cap in turn exhibit interiorly configured

surfaces, see at 80 and 82, for matingly interengaging with the exteriorly configured surfaces associated with the wings 30 and 32 upon downward installation of the cap 68 in the direction of arrow 84 in Figs. 4 and 5 and in order to securely engage the cap 68 over the folded main body 26, and the main
5 body in turn over and between the reclosable portions 12 and 14 of the bag 16.

Having described my invention, other and additional preferred embodiments will become apparent to those skilled in the art to which it pertains and without deviating from the scope of the appended claims. In particular, it is also envisioned that a strap (not shown) can interconnect the cap
10 68 to the main body 26 and such that it facilitates quicker manual assembly of the slider assembly over the resealable bag portions.

I claim: